§ 98.298

- (1) Monthly production of soda ash (tons)
- (2) Monthly consumption of trona or liquid alkaline feedstock (tons)
 - (3) Annual operating hours (hours).
- (b) If a CEMS is not used to measure emissions, then you must retain records for the information listed in this paragraph (b):
- (1) Records of all analyses and calculations conducted for determining all reported data as listed in §98.296(b).
- (2) If using Equation CC-1 or CC-2 of this subpart, weekly inorganic carbon content factor of trona or soda ash, depending on method chosen, as measured by the applicable method in §98.294(b) (percent by weight expressed as a decimal fraction).
- (3) Annual operating hours for each manufacturing line used to produce soda ash (hours).
- (4) You must document the procedures used to ensure the accuracy of the monthly trona consumption or soda ash production measurements including, but not limited to, calibration of weighing equipment and other measurement devices. The estimated accuracy of measurements made with these devices must also be recorded, and the technical basis for these estimates must be provided.
- (5) If you produce soda ash using the liquid alkaline feedstock process and use the site-specific emission factor method to estimate emissions (§98.293(b)(3)) then you must also retain the following relevant information:
- (i) Records of performance test results.
- (ii) You must document the procedures used to ensure the accuracy of the annual average vent flow measurements including, but not limited to, calibration of flow rate meters and other measurement devices. The estimated accuracy of measurements made with these devices must also be recorded, and the technical basis for these estimates must be provided.

§ 98.298 Definitions.

All terms used in this subpart have the same meaning given in the Clean Air Act and subpart A of this part.

Subpart DD—Electrical Transmission and Distribution Equipment Use

SOURCE: 75 FR 74855, Dec. 1, 2010, unless otherwise noted.

§ 98.300 Definition of the source category.

- (a) The electrical transmission and distribution equipment use source category consists of all electric transmission and distribution equipment and servicing inventory insulated with or containing sulfur hexafluoride (SF₆) or perfluorocarbons (PFCs) used within an electric power system. Electric transmission and distribution equipment and servicing inventory includes, but is not limited to:
 - (1) Gas-insulated substations.
 - (2) Circuit breakers.
- (3) Switchgear, including closed-pressure and hermetically sealed-pressure switchgear and gas-insulated lines containing SF_6 or PFCs.
- (4) Gas containers such as pressurized cylinders.
 - (5) Gas carts.
 - (6) Electric power transformers.
 - (7) Other containers of SF_6 or PFC.

§98.301 Reporting threshold.

- (a) You must report GHG emissions from an electric power system if the total nameplate capacity of SF_6 and PFC containing equipment (excluding hermetically sealed-pressure equipment) located within the facility, when added to the total nameplate capacity of SF_6 and PFC containing equipment (excluding hermetically sealed-pressure equipment) that is not located within the facility but is under common ownership or control, exceeds 17,820 pounds and the facility meets the requirements of $\S 98.2(a)(1)$.
- (b) A facility other than an electric power system that is subject to this part because of emissions from any other source category listed in Table A-3 or A-4 in subpart A of this part is not required to report emissions under subpart DD of this part unless the total nameplate capacity of SF₆ and PFC containing equipment located within that facility exceeds 17,820 pounds.